

#### CAUTION

Use under well ventilated conditions. Keep away from heat, sparks and open flame.

#### FIRST AID TREATMENT

Contains Methyl ethyl ketone, n-Hexane, Petroleum distillates, Toluene and Cyclohexane. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for at least 15 minutes. If on skin, rinse well with water.

#### INSTRUCTIONS

1. Wipe vinyl plastic surface to be repaired with clean cloth.
2. For rubber repairs only roughen damaged area with metal buffer, then wipe surface with clean cloth.
3. Apply cement. Spread evenly over an area 50% larger than patch to be applied. Let dry 1 minute.
4. Use ready cut bevels for small repairs. For larger holes or tears, cut piece of patching material large enough to overlap injury  $\frac{1}{2}$ " to 1". for best results round corners.
5. Remove protective material from patch by tearing down the middle, remove half at a time. Do not touch adhesive surface. Center patch over injury and press down firmly with thumbs or edge of coin to drive out trapped air.
6. For best results **LET SET FOR 20 MINUTES BEFORE USE.**

#### KEEP OUT OF REACH OF CHILDREN

**WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

---

#### Contents

- 8.8 mL (.30 fl. oz.) Cement; 1 Metal Rasp;  
4 - 3.18 x 3.18 cm (1 $\frac{1}{4}$ " x 1 $\frac{1}{4}$ ") Rubber Patches;  
1 - 6.35 x 10.16 cm (2 $\frac{1}{2}$ " x 4") Rubber Patch.



Made in U.S.A. / Printed in U.S.A.  
© 2004 Coghlan's Ltd. Winnipeg, Canada R3T 4C7